

## ■ 定格総荷重表

## ▶ ジブ定格総荷重表 (主フックなし ジブ取付角度10°)

(単位:t)

ブーム長さ (m) 作業 半径(m)	33.5			36.6			39.6			42.7		
	9.1	15.2	21.3	9.1	15.2	21.3	9.1	15.2	21.3	9.1	15.2	21.3
10.0	11.0/10.0m			11.0/10.6m			11.0/11.1m			11.0/11.6m		
12.0	11.0	8.0/12.1m	4.3/13.6m	11.0	8.0/12.7m		11.0	8.0/13.2m		11.0	8.0/13.7m	
14.0	11.0	8.0	4.3	11.0	8.0	4.3/14.1m	11.0	8.0	4.3/14.7m	11.0	8.0	4.3/15.2m
16.0	11.0	8.0	4.3	11.0	8.0	4.3	11.0	8.0	4.3	11.0	8.0	4.3
18.0	10.4	8.0	4.3	10.4	8.0	4.3	10.3	8.0	4.3	10.1	8.0	4.3
20.0	9.0	8.0	4.3	8.7	8.0	4.3	8.8	8.0	4.3	8.6	8.0	4.3
22.0	7.8	8.0	4.3	7.7	8.0	4.3	7.6	7.9	4.3	7.4	7.7	4.3
24.0	6.8	7.1	4.3	6.7	7.0	4.3	6.6	6.9	4.3	6.5	6.7	4.3
26.0	6.0	6.3	4.3	5.9	6.2	4.3	5.8	6.1	4.3	5.7	5.9	4.3
28.0	5.3	5.6	4.3	5.2	5.5	4.3	5.1	5.4	4.3	5.0	5.2	4.3
30.0	4.8	5.0	4.3	4.7	4.9	4.3	4.6	4.8	4.3	4.4	4.6	4.3
32.0	4.2	4.5	4.3	4.2	4.4	4.3	4.1	4.3	4.3	3.9	4.1	4.2
34.0	3.8	4.0	4.1	3.7	3.9	4.0	3.6	3.8	3.9	3.4	3.7	3.8
36.0	3.4	3.6	3.7	3.3	3.5	3.6	3.2	3.4	3.5	3.0	3.3	3.4
38.0	3.1	3.3	3.4	3.0	3.2	3.3	2.9	3.1	3.2	2.7	2.9	3.0
40.0	3.0/39.0m	3.0	3.1	2.7	2.9	3.0	2.6	2.8	2.9	2.4	2.6	2.7
42.0		2.7	2.8	2.4	2.6	2.7	2.3	2.5	2.6	2.0	2.3	2.4
44.0		2.4	2.5	1.8	2.3	2.4	2.0	2.2	2.3	1.7	2.0	2.2
46.0		2.3/44.8m	2.3	1.5/44.9m	2.1	2.2	1.9/44.4m	2.0	2.1	1.5/46.0m	1.7	1.9
48.0			2.1		1.9/47.5m	2.0		1.7	1.8		1.5/48.0m	1.6
50.0			1.5/49.7m			1.8		1.5/50.0m	1.6			1.5/49.0m
52.0						1.5/52.0m			1.5/51.0m			

(単位:t)

ブーム長さ (m) 作業 半径(m)	45.7			48.8			51.8		
	9.1	15.2	21.3	9.1	15.2	21.3	9.1	15.2	21.3
10.0									
12.0	11.0/12.1m			11.0/12.7m			11.0/13.2m		
14.0	11.0	8.0/14.2m	4.3/15.7m	11.0	8.0/14.8m		11.0	8.0/15.3m	
16.0	11.0	8.0	4.3	11.0	8.0	4.3/16.3m	11.0	8.0	4.3/16.8m
18.0	10.1	8.0	4.3	10.1	8.0	4.3	10.0	8.0	4.3
20.0	8.6	8.0	4.3	8.6	8.0	4.3	8.5	8.0	4.3
22.0	7.4	7.7	4.3	7.4	7.7	4.3	7.2	7.5	4.3
24.0	6.5	6.7	4.3	6.4	6.7	4.3	6.2	6.5	4.3
26.0	5.6	5.9	4.3	5.6	5.8	4.3	5.4	5.7	4.3
28.0	4.9	5.2	4.3	4.9	5.1	4.3	4.7	4.9	4.3
30.0	4.3	4.6	4.3	4.3	4.5	4.3	4.1	4.3	4.3
32.0	3.8	4.1	4.2	3.7	4.0	4.1	3.6	3.8	3.9
34.0	3.4	3.6	3.7	3.3	3.5	3.6	3.1	3.3	3.5
36.0	3.0	3.2	3.3	2.8	3.1	3.2	2.6	2.9	3.0
38.0	2.5	2.8	2.9	2.4	2.7	2.9	2.1	2.5	2.6
40.0	2.1	2.4	2.6	2.0	2.3	2.5	1.8	2.1	2.2
42.0	1.8	2.1	2.2	1.7/42.0m	2.0	2.1	1.5/41.5m	1.7	1.9
44.0	1.5/44.0m	1.8	1.9		1.6	1.8		1.5/43.5m	1.6
46.0		1.5/46.0m	1.6		1.5/44.7m	1.5/46.0m			1.5/44.6m
48.0			1.5/47.0m						
50.0									
52.0									

表中の太線で囲まれた部分は、ブーム等の強度によって定められた値です。