

## ■ 定格総荷重表

## ▶ ジブ定格総荷重表 (主フックなし ジブ取付角度30°)

(単位:t)

ブーム長さ (m) 作業 半径(m)	33.5			36.6			39.6			42.7		
	9.1	15.2	21.3	9.1	15.2	21.3	9.1	15.2	21.3	9.1	15.2	21.3
12.0	9.3/12.8m			9.3/13.3m								
14.0	9.3			9.3			9.3/14.0m			9.3/14.3m		
16.0	9.3	5.0/16.7m		9.3	5.0/17.2m		9.3	5.0/17.7m		9.3		
18.0	9.3	5.0		9.3	5.0		9.3	5.0		9.3	5.0/18.2m	
20.0	9.3	5.0	3.1/20.2m	9.2	5.0	3.1/20.6m	9.2	5.0	3.1/21.1m	9.0	5.0	3.1/21.7m
22.0	8.1	5.0	3.1	8.0	5.0	3.1	7.9	5.0	3.1	7.8	5.0	3.1
24.0	7.1	5.0	3.1	7.0	5.0	3.1	6.9	5.0	3.1	6.8	5.0	3.1
26.0	6.2	5.0	3.1	6.2	5.0	3.1	6.1	5.0	3.1	5.9	5.0	3.1
28.0	5.5	5.0	3.1	5.4	5.0	3.1	5.4	5.0	3.1	5.2	5.0	3.1
30.0	4.9	5.0	3.1	4.8	5.0	3.1	4.7	5.0	3.1	4.6	5.0	3.1
32.0	4.4	4.7	3.1	4.3	4.6	3.1	4.2	4.6	3.1	4.1	4.4	3.1
34.0	3.9	4.2	3.1	3.8	4.2	3.1	3.8	4.1	3.1	3.6	3.9	3.1
36.0	3.5	3.8	3.1	3.4	3.7	3.1	3.3	3.7	3.1	3.2	3.5	3.1
38.0	3.1	3.4	3.0	3.1	3.4	3.0	3.0	3.3	3.0	2.8	3.1	3.0
40.0	2.8/39.7m	3.1	2.9	2.7	3.0	2.9	2.6	2.9	2.9	2.5	2.8	2.9
42.0		2.8	2.8	2.4	2.7	2.8	2.4	2.6	2.7	2.2	2.5	2.7
44.0		2.5	2.7	2.3/42.3m	2.4	2.6	2.1	2.4	2.5	1.8	2.2	2.4
46.0		2.2/45.8m	2.5		2.2	2.4	1.9/45.0m	2.1	2.3	1.5/46.0m	1.9	2.2
48.0			2.2		1.9/48.0m	2.2		1.8	2.0		1.6	1.9
50.0			2.0			1.9		1.5/50.0m	1.8		1.5/49.0m	1.6
52.0			1.8/51.9m			1.7			1.6			1.5/51.0m
54.0						1.5/54.0m			1.5/52.6m			

(単位:t)

ブーム長さ (m) 作業 半径(m)	45.7			48.8			51.8		
	9.1	15.2	21.3	9.1	15.2	21.3	9.1	15.2	21.3
12.0									
14.0	9.3/14.9m			9.3/15.4m					
16.0	9.3			9.3			9.3/16.0m		
18.0	9.3	5.0/18.8m		9.3	5.0/19.3m		9.3		
20.0	9.0	5.0		9.0	5.0		9.0	5.0/20.0m	
22.0	7.8	5.0	3.1/22.2m	7.8	5.0	3.1/22.7m	7.7	5.0	3.1/23.2m
24.0	6.8	5.0	3.1	6.8	5.0	3.1	6.6	5.0	3.1
26.0	5.9	5.0	3.1	5.9	5.0	3.1	5.7	5.0	3.1
28.0	5.2	5.0	3.1	5.1	5.0	3.1	5.0	5.0	3.1
30.0	4.6	5.0	3.1	4.5	4.9	3.1	4.4	4.8	3.1
32.0	4.0	4.4	3.1	4.0	4.4	3.1	3.8	4.2	3.1
34.0	3.5	3.9	3.1	3.5	3.9	3.1	3.3	3.7	3.1
36.0	3.1	3.5	3.1	3.1	3.4	3.1	2.9	3.3	3.1
38.0	2.7	3.1	3.0	2.6	3.0	3.0	2.4	2.9	3.0
40.0	2.3	2.7	2.9	2.2	2.7	2.9	2.0	2.5	2.8
42.0	1.9	2.4	2.7	1.8	2.3	2.6	1.6	2.1	2.4
44.0	1.6	2.0	2.3	1.5/44.0m	1.9	2.3	1.5/42.6m	1.7	2.1
46.0	1.5/44.6m	1.7	2.0		1.6	1.9		1.5/45.6m	1.7
48.0		1.5/47.5m	1.7/48.0m		1.5/46.6m	1.6/48.0m			1.5/47.3m
50.0									
52.0									
54.0									

表中の太線で囲まれた部分は、ブーム等の強度によって定められた値です。