

■定格総荷重表

■28.65mタワー

(単位：t)

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)				タワー角度 (°)				タワー角度 (°)				タワー角度 (°)			
	90		80		70		60		90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2	20.0	11.0/9.7														
10.0	20.0	11.0							18.6	11.0/10.5						
12.0	20.0	11.0							18.6	11.0						
14.0	20.0	11.0							18.6	11.0						
15.0	18.5	11.0							18.2	11.0						
16.0	17.2	11.0	16.5/16.7	11.0/17.3					17.0	11.0	15.0/17.9					
18.0	15.1	11.0	15.1	11.0					14.9	11.0	14.9	11.0/18.4				
20.0	13.5	11.0	13.5	11.0					13.3	11.0	13.3	11.0				
22.0	12.3	11.0	12.3	11.0					12.0	11.0	12.0	11.0				
24.0	10.2	10.2	11.2	11.0	10.8/24.9	10.5/25.6			11.0	11.0	11.0	11.0				
26.0	8.7/24.6	8.7/25.6	10.3	10.3	10.3	10.3			10.1	10.1	10.1	10.1	9.9/26.5	9.6/27.2		
28.0			9.6	9.6	9.6	9.6			7.6/27.5	7.6	9.3	9.3	9.3	9.3		
30.0			9.2/29.5	9.0	9.0	9.0			7.6/28.5	8.7	8.7	8.7	8.7	8.7		
32.0				8.9/30.5	8.4	8.4	8.2/32.3	8.0/33.1			8.1	8.1	8.1	8.1		
34.0					7.9	7.9	7.9	7.9			8.0/32.5	7.7/33.5	7.6	7.6	7.5/34.4	7.4/35.1
36.0					7.8/34.3	7.6/35.3	7.4	7.4					7.2	7.2	7.2	7.2
38.0							7.0	7.0					7.0/37.2	6.8	6.8	6.8
40.0							6.9/38.7	6.7/39.6						6.8/38.2	6.4	6.4
42.0															6.1/41.6	6.0
44.0																5.9/42.6

■31.70mタワー

作業半径 (m)	タワージブ長さ (m)															
	22.85								25.90							
	タワー角度 (°)				タワー角度 (°)				タワー角度 (°)				タワー角度 (°)			
	90		80		70		60		90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2	20.0	11.0/9.7														
10.0	20.0	11.0							18.6	11.0/10.5						
12.0	20.0	11.0							18.6	11.0						
14.0	19.9	11.0							18.6	11.0						
15.0	18.4	11.0							18.2	11.0						
16.0	17.1	11.0	15.8/17.2	11.0/17.8					16.9	11.0						
18.0	15.0	11.0	15.0	11.0					14.8	11.0	14.5/18.4	11.0/19.0				
20.0	13.4	11.0	13.4	11.0					13.2	11.0	13.2	11.0				
22.0	12.1	11.0	12.1	11.0					11.9	11.0	11.9	11.0				
24.0	10.3	10.3	11.0	11.0	10.1/25.9				10.8	10.8	10.8	10.8				
26.0	8.8/24.6	8.8/25.6	10.1	10.1	10.1	9.9/26.6			9.9	9.9	9.9	9.9	9.4/27.5			
28.0			9.4	9.4	9.4	9.4			7.8/27.5	7.8	9.2	9.2	9.2	9.1/28.2		
30.0			8.7	8.7	8.7	8.7			7.8/28.5	8.5	8.5	8.5	8.5			
32.0				8.5/31.0	8.2	8.2	7.8/33.8				7.9	7.9	7.9			
34.0					7.7	7.7	7.7	7.6/34.6			7.7/33.0	7.4	7.4	7.4	7.0/35.9	
36.0					7.4/35.3	7.2	7.2	7.2					7.0	7.0	7.0	6.8/36.7
38.0						7.1/36.3	6.8	6.8					6.5	6.5	6.5	6.5
40.0							6.4	6.4					6.5/38.2	6.3/39.2	6.2	6.2
42.0								6.4/40.2	6.2/41.2						5.8	5.8
44.0															5.6/43.1	5.5
46.0																5.4/44.1

作業半径 (m)	タワージブ長さ (m)							
	28.95							
	タワー角度 (°)				タワー角度 (°)			
	90		80		70		60	
	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛	2本掛	1本掛
9.2								
10.0	15.4/10.8	11.0/11.3						
12.0	15.4	11.0						
14.0	15.4	11.0						
15.0	15.4	11.0						
16.0	15.4	11.0						
18.0	14.6	11.0	13.4/19.5					
20.0	13.0	11.0	13.0	11.0/20.1				
22.0	11.7	11.0	11.7	11.7				
24.0	10.6	10.6	10.6	10.6				
26.0	9.7	9.7	9.7	9.7				
28.0	9.0	9.0	9.0	9.0	8.6/29.1	8.4/29.8		
30.0	7.4	7.4	8.3	8.3	8.3	8.3		
32.0	6.8/30.4	6.8/31.4	7.7	7.7	7.7	7.7		
34.0			7.2	7.2	7.2	7.2		
36.0			6.8/35.9	6.8	6.8	6.8	6.4/37.9	
38.0				6.6/36.9	6.4	6.4	6.4	6.3/38.7
40.0					6.0	6.0	6.0	6.0
42.0					5.8/41.2	5.6	5.6	5.6
44.0						5.6/42.2	5.3	5.3
46.0							5.0	5.0
48.0							5.0/46.1	4.8/47.1